



Project Name	
Type	
Part Number	
Quantity	
Notes	

## Product Overview

The Reed RD2 is a recessed wall luminaire with a slim, vertical rectangular profile. It provides over 200 delivered lumens in a forward throw distribution with a medium narrow beam. Multiple fittings can be used to effectively illuminate wide pathways, stairways and cycleways. A Dark Sky option is available.

## Features


Lumen Output	215 lm
Power Consumption	< 9 W
Typical Lifetime	> 60,000 hrs (B10, L70, TM21 Reported)
Input Voltage	International: 220-240 Vac, 50 Hz   North America: 120/277 Vac, 60 Hz
Control Protocols	DALI, 0-10 V
Weight	1.2 lb (0.5 kg)
IP Rating	IP66/67
IK Rating	IK9
BUG Rating	B0-U2-G1
Compliance	    
Color Options	 

## Specifications

LS1252





### Dimensions - LS1252



### DarkSky Option

Fitting must be Black or Graphite Grey, have a light source with a CCT of 3000K or 2700K and must include a glare shield in Black or Graphite Grey. Refer to page 6 for configuration of DarkSky option.

### Glare Shield



## Configuration

For complete and up-to-date product options, configure the LS1252 using our online [product configurator](#).

LS1252							
Code	Power Consumption	Light Source	Style	Beam Angles	Input Voltage	Control	Finish

### Power Consumption

For all PowerSync Controlled Luminaires

- 9 W (09D)**  
9 W

### Light Source

- Static White (827)**  
2,700 K (80 CRI, 3 SDCM)
- Static White (830)**  
3,000K (80 CRI, 3 SDCM)
- Static White (840)**  
4,000 K (80 CRI, 3 SDCM)

### Style

- Recessed Baffle (RB)**  
Recessed Baffle

### Beam Angles

Published angles may vary slightly to photometric data. Please refer to IES files where relevant.

- Medium Throw (MD)**  
50° x 30° 

### Input Voltage

- 220 to 240 Vac, 50 Hz (01)**  
Line Voltage 
- 120/277 Vac, 60 Hz (09)**  
Line Voltage 

Control

- DALI (DL)
- 0-10V (AH)

Finish

Custom powder coat colours are available. Please consult factory.

- |  |   |   |   |   |   |
|--|---|---|---|---|---|
| <input type="checkbox"/> <b>Black (BL)</b><br>RAL9004 from RAL<br>Classic collection<br>(formerly CB)  |    | <input type="checkbox"/> <b>Anthracite Gray (AG)</b><br>RAL7016 from RAL<br>Classic collection                |  | <input type="checkbox"/> <b>Basalt Gray (BT)</b><br>RAL7012 from RAL<br>Classic collection    |  |
| <input type="checkbox"/> <b>Graphite Gray (GH)</b><br>Graphite Gray  |    | <input type="checkbox"/> <b>Anodic Silver (SL)</b><br>RAL9006 from RAL<br>Classic collection<br>(formerly CS) |  | <input type="checkbox"/> <b>White (WT)</b><br>RAL9016 from RAL<br>Classic collection          |  |
| <input type="checkbox"/> <b>Dark Bronze (DB)</b><br>RAL8019 from RAL<br>Classic collection   |    | <input type="checkbox"/> <b>Latte (LT)</b><br>RAL7006 from RAL<br>Classic collection                          |  | <input type="checkbox"/> <b>Dark Aluminium (DA)</b><br>RAL9007 from RAL<br>Classic collection |  |
| <input type="checkbox"/> <b>Custom RAL (CC)</b><br>A one-off custom color<br>setup fee applies. Click<br>on 'More Info' button to<br>add to your enquiry.<br>Contact Lumascape for<br>volume discount on set-<br>up fee. |  |   |   |   |   |

## Accessories

### Required Pre-Installation Kit

Specify Separately

- Pre-Installation Kit (LS6335)**  
 Required pre-installation  
 kit used for mounting  
 the Reed RD2 on any  
 flat surface.



### Custom Color

A one-off setup fee applies for each custom color per order. Add to your enquiry.

- Custom Color Setup Fee (Custom RAL Color)**  
 Custom RAL colour  
 setup fee



## Dark Sky Configuration



For complete and up-to-date product options, configure the LS1252 using our online product configurator.

LS1252	09D		RB	DY			
Code	Power Consumption	Light Source	Style	Beam Angles	Input Voltage	Control	Finish

Must add Accessories:

LS6335
Mounting

### Power Consumption

For all PowerSync Controlled Luminaires

- 9 W (09D)  
9 W

### Light Source

- Static White (827)  
2,700 K (80 CRI, 3 SDCM)

- Static White (830)  
3,000K (80 CRI, 3 SDCM)



### Style

- Recessed Baffle (RB)  
Recessed Baffle

### Beam Angles

Published angles may vary slightly to photometric data. Please refer to IES files where relevant.

- DarkSky (DY)

### Input Voltage

- 220 to 240 Vac, 50 Hz (01)  
Line Voltage



- 120/277 Vac, 60 Hz (09)  
Line Voltage



Control

- DALI (DL)  0-10V (AH)

Finish

Custom powder coat colours are available. Please consult factory.

- Black (BL)**  
RAL9004 from RAL  
Classic collection  
(formerly CB) 
- Graphite Gray (GH)**  
Graphite Gray 

Accessories

Required Pre-Installation Kit

Specify Separately

- Pre-Installation Kit (LS6335)**  
Required pre-installation kit used for mounting the Reed RD2 on any flat surface. 